

s t r o n g
u n d e r
f i r e



**DUAL OVENABLE
CPET CONTAINERS**

FROM GAGE



DUAL OVENABLE CPET CONTAINERS

Freezer Safe to -40°F • Oven Safe to 400°F for 30 minutes • Microwavable

	PART NUMBER	DESCRIPTION	DIMENSIONS	LID	UNITS/ CASE	CASES/ PALLET	CASE WEIGHT
	GPC-3047	5 fl. oz. Oval Tray	3.09" x 4.65" x 1.41"	No	1920	24	34 lbs.
	GPC-4500-MB	7.5 fl. oz. Mini Bake Cup	4.5" round x 1.91"	No	1500	25	33 lbs.
	GPC-5200-14	14 fl. oz. Bowl	5.2" round x 1.815"	No	1035	25	40 lbs
	GPC-5800	20.5 fl. oz. Round Tray	5.4" round x 1.83"	No	680	28	42 lbs
	GPC-6300-16	16 fl. oz. Bowl	6.3" round x 1.5"	Yes	690	42	29 lbs.
	GPC-6300-16S	16 fl. oz Bowl	6.3" round x 1.5"	Yes	390	42	19 lbs.
	GPC-6300-19C	19 fl. oz. Bowl	6.3" round x 1.875"	Yes	690	42	31 lbs.
	GPC-6300-20	20 fl. oz. Bowl	6.3" round x 1.875"	Yes	690	42	31 lbs.
	GPC-6300-20S	20 fl. oz. Bowl	6.3" round x 1.875"	Yes	390	42	19 lbs.
	GPC-6800	14 fl. oz. Round Tray	6.8" round x .875"	No	660	36	24 lbs.
	GPC-5877-1-100	14 fl. oz. Oval Tray	5.8" x 7.68" x 1"	No	540	28	25 lbs.
	GPC-5877-1-125	17 fl. oz. Oval Tray	5.8" x 7.68" x 1.25"	No	540	28	25 lbs.
	GPC-5877-2-125	10.5/5.5 fl. oz. Oval Tray	5.8" x 7.68" x 1.25"	No	540	28	25 lbs.

Colors: Black is standard, almond is available. Your custom designs are encouraged.

	PART NUMBER	DESCRIPTION	DIMENSIONS	LID	UNITS/ CASE	CASES/ PALLET	CASE WEIGHT
	GPC-5066-12	12 fl. oz. Tray	5" x 6.625" x 1"	Yes	600	28	25 lbs.
	GPC-5066-16	16 fl. oz. Tray	5" x 6.625" x 1.5"	Yes	600	28	25 lbs.
	GPC-5066-22	22 fl. oz. Tray	5" x 6.625" x 2.0"	Yes	600	28	29 lbs.
	GPC-5066-25	24.5 fl. oz. Tray	5" x 6.625" x 2.4"	Yes	600	28	29 lbs.
	GPC-6585-1F-125	23.5 fl. oz. Tray	6.5" x 8.5" x 1.25"	Yes	420	30	33 lbs.
	GPC-6585-1FM	32 fl. oz. Tray	6.5" x 8.5" x 1.5"	Yes	390	30	31 lbs.
	GPC-6585-1F	40 fl. oz. Tray	6.5" x 8.5" x 1.875"	Yes	390	30	31 lbs.
	GPC-6585-1FD	45 fl. oz. Tray	6.5" x 8.5" x 2.125"	Yes	390	30	36 lbs.
	GPC-6585-1F-325	65.5 fl. oz. Tray	6.5" x 8.5" x 3.25"	Yes	420	30	42 lbs.
	GPC-6585-1F-400	78.5 fl. oz. Tray	6.5" x 8.5" x 4.0"	Yes	390	30	43 lbs.
	GPC-6585-2FM	15.5/11.5 fl. oz. Tray	6.5" x 8.5" x 1.5"	Yes	390	30	31 lbs.
	GPC-6585-2F	21/15 fl. oz. Tray	6.5" x 8.5" x 1.875"	Yes	390	30	31 lbs.
	GPC-6585-2F-250	27/19 fl. oz. Tray	6.5" x 8.5" x 2.50"	Yes	450	30	45 lbs.
	GPC-6585-3FM	17/5/5 fl. oz. Tray	6.5" x 8.5" x 1.5"	Yes	390	30	33 lbs.
	GPC-6585-3F	21/6/6 fl. oz. Tray	6.5" x 8.5" x 1.875"	Yes	390	30	31 lbs.
	GPC-6585-3R	21/6/6 fl. oz. Tray	6.5" x 8.5" x 1.875"	Yes	390	30	31 lbs.
	GPC-68128-60	60 fl. oz. 1/3 VFT	6.88" x 12.75" x 1.875"	Yes	250	30	36 lbs.
	GPC-10125-1-250	140 fl. oz. 1/2 VFT	10" x 12.5" x 2.50"	No	160	28	34 lbs.
	GPC-10125-1-350	166 fl. oz. 1/2 VFT	10" x 12.5" x 3.50"	No	150	28	34 lbs.

Dual Ovenable CPET Usage Guidelines

CPET Baking and Heating Instructions

- Gage CPET containers are designed to withstand conventional oven temperatures of 400°F for 30 minutes. Please note time and temperature constraints may vary due to different oven types and controls.
- Lidding films that are not self-venting should be cut or punctured or removed over each food compartment to vent steam during cooking. Failure to do so may cause damage to container integrity.
- Containers must be placed on a baking sheet for heating in the center of a preheated conventional oven. After heating, remove baking sheet and container from conventional oven and allow cooling for two minutes before handling.
- Containers should be placed on a microwave-safe plate for heating in a microwave oven. After heating allow tray to cool for two minutes prior to handling.
- Do not place containers directly on oven rack.
- All baking tests or container evaluations should be performed in an oven with product present in container.
- Do not expose containers to direct contact with open flame or oven heating elements. For example, not for use in toaster ovens, broilers or barbeque grills.

- Gage CPET containers are to be used only once. Do not re-use containers, as multiple heat applications could change the integrity of the container.

APET Lid Recommendations

- Gage APET lids should never be placed in a conventional oven or microwave oven when heating or baking product.
- Heated food must be cooled before covering with an APET lid.

Freezing Recommendations

- Gage CPET containers are break resistant, designed to withstand temperatures reaching -40°F .
- Proper handling must be exercised with frozen CPET products. In shipping, mark "Handle with Care."

Lidding Film Sealing Recommendations

- Gage CPET containers are compatible with a variety of lidding films. We recommend the sealing area (flange) be dry and clear of foreign matter to ensure maximum sealing integrity.
- Do not reseal containers.

GAGE INDUSTRIES, INC.

Corporate Headquarters
6710 McEwan Road
Lake Oswego, OR 97035
USA

503.639.2177
800.443.4243

www.gageindustries.com

